




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification<sup>4</sup> :</b>  <b>G01N 21/53</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 87/ 06697</b>  <b>(43) International Publication Date:</b> 5 November 1987 (05.11.87)
<b>(21) International Application Number:</b> PCT/US87/00916 <b>(22) International Filing Date:</b> 23 April 1987 (23.04.87) <b>(31) Priority Application Number:</b> 855,808 <b>(32) Priority Date:</b> 24 April 1986 (24.04.86) <b>(33) Priority Country:</b> US  <b>(71) Applicant:</b> PACIFIC SCIENTIFIC COMPANY [US/US]; 2431 Linden Lane, Silver Spring, MD 20910 (US). <b>(72) Inventor:</b> GROSS, Kenneth, P. ; 69 Coronado Avenue, San Carlos, CA 94070 (US). <b>(74) Agents:</b> AITKEN, Richard, L. et al.; Lane & Aitken, 2600 Virginia Avenue, N.W., Washington, DC 20037 (US).		<b>(81) Designated States:</b> AT (European patent), BE (European patent), CH (European patent), DE (European patent), DK, FR (European patent), GB (European patent), IT (European patent), JP, LU (European patent), NL (European patent), NO, SE (European patent).  Published <i>With international search report.</i>

**(54) Title:** PARTICLE COUNTER AIR INLET ASSEMBLY**(57) Abstract**

The sample air inlet nozzle (18) into a particle counter test cell (10) is formed with an elongated, flattened tip (18a) to provide a thin, flat laminar flow jet (19) which intersects a laser beam (14). A secondary tube (24) surrounding the nozzle provides a sheath of air which helps maintain the jet shape.

***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	ML	Mali
AU	Australia	GA	Gabon	MR	Mauritania
BB	Barbados	GB	United Kingdom	MW	Malawi
BE	Belgium	HU	Hungary	NL	Netherlands
BG	Bulgaria	IT	Italy	NO	Norway
BJ	Benin	JP	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	LI	Liechtenstein	SN	Senegal
CH	Switzerland	LK	Sri Lanka	SU	Soviet Union
CM	Cameroon	LU	Luxembourg	TD	Chad
DE	Germany, Federal Republic of	MC	Monaco	TG	Togo
DK	Denmark	MG	Madagascar	US	United States of America
FI	Finland				

-1-

## PARTICLE COUNTER AIR INLET ASSEMBLY

Field of the Invention

This invention relates to instruments for detecting, counting or otherwise measuring particles in fluids, particularly air. More specifically, the invention relates to an improved airflow system in such an instrument.

Background of the Invention

Instruments for measuring particles in air are utilized in an increasing number of situations. Perhaps the single largest field of use is in the semiconductor industry wherein cleanliness in fabricating semiconductors is extremely important. For example, particle counters are utilized to monitor the number of particles in so called clean rooms in which semi-conductor manufacturing operations are conducted. Clean rooms are usually classified on the basis of the maximum number of particles of a given size permitted per volume of air. To meet specifications and maintain quality levels of the product being made, it is necessary to ensure that particle contamination is kept to an acceptable minimum requirement.

The basic system utilized in most airborne particle counters transmits a sample air stream through a beam of light, which results in light energy being scattered by the particles. This energy is detected and measured by suitable optics and electronics. Significant improvements have been made in the optics and electronics employed for detecting and processing the scattered light signals. Also, the advent of lasers has greatly improved the quality and intensity of the illuminating light beam.

In spite of these improvements, the accuracy of the data output from the instruments still leaves much to be desired. For example, in testing or calibrating particle counters, one technique employed is to inject a sample jet stream through the instrument that carries only particles

-2-

of a known size. Output signals from such a test sample should be fairly uniform. However, it has been found that typically such results are not very uniform. Similar tests also reveal other inaccuracies, such as  
5 recirculating particles and appreciable discrepancies in absolute count correlation between different instruments. Thus, further improvements of particle counters are needed.

It is believed that one area of the instrument that 10 has not received sufficient attention is the system for providing the sample air jet that flows into the instrument. One type of previously used nozzle is simply a tube with a circular cross section. Another type employs a tube with a circular cross section having a  
15 short tip with a generally rectangular cross section to fit within the diameter of the light beam. One nozzle of that type was made fairly precise by investment casting. In another arrangement, the end of a circular tube was pinched by a suitable tool to be less than the diameter of  
20 the light beam. A tube surrounding a nozzle for focusing or otherwise confining the jet has been used. These lack some uniformity of results. Thus, a need exists for improving the sample airflow delivery system.

#### Summary of the Invention

25 Briefly stated, the present invention comprises a particle counter with an improved gas delivery system which provides a sample gas jet that consistently has a laminar and well defined flow as it passes through the sensing zone of the light beam. The laminar flow is  
30 desirable for a variety of reasons. In order to have an accurate instrumental evaluation, it is, of course, necessary that all of the particles in the sample flow through the light beam. Thus, it is necessary that the jet remain precise and well controlled as it passes  
35 through the beam. Secondly, turbulence in the sample jet boundary layer can cause recirculation of particles,

-3-

which, of course, results in an inaccurate count. Recirculation can also contaminate mirrors or other optical elements in the test cell, resulting in errors in the readings and requiring frequent cleaning. Further, substantial turbulence in the jet flow can actually disturb the laser beam characteristics, and in fact can critically affect the laser power and stability in applications utilizing "open-cavity" laser resonators. The sample gas is introduced into the test cell of the instrument by means of a nozzle having an elongated tip with a flattened constant cross section. It has been found that such an elongated tip provides greatly improved results over previously used nozzle tips. Preferably, this flattened tip extends at least three times the longer dimension of the nozzle tip interior cross section or extends at least a half inch with a substantially constant cross section.

In addition to the use of an elongated flattened nozzle tip, the gas delivery system of the invention employs a separate tube surrounding the nozzle. Filtered gas flows through this tube to help confine the jet within its original boundaries without reducing or focusing effects.

#### Description of the Drawings

Figure 1 is a schematic view of a portion of a particle counter illustrating the invention;

Figure 2 is a side elevational schematic view of the apparatus of Figure 1;

Figure 3 is a perspective view of the nozzle of Figures 1 and 2 illustrating the dimensions of the flattened tip;

Figure 4 is an enlarged, perspective, schematic view of the nozzle tip within its co-flow tube, and with an air jet passing through a light beam.

-4-

Figure 5 is an enlarged edge view of the nozzle and co-flow tube schematically illustrating the air jet of Figure 4 passing through the light beam;

Figure 6 is an enlarged fragmentary end view of the flattened tip of one size of the nozzle, showing an edge of the tip; and

Figure 7 is a view similar to Figure 6 of a nozzle tip which is even thinner than that of Figure 6.

#### Detailed Description of the Drawings

10 Referring to Figure 1, there is schematically shown a portion of an optical particle counter utilizing an open-cavity laser design, including a main sensor cell body 10, laser plasma tube 12, and ancillary cavity end-mirror 16, which define the intracavity light beam axis 15 of the  
15 illuminating radiation 14.

An air inlet nozzle 18 introduces a jet of air 19 into the cell body 10, such air jet carrying particles to be detected. While the primary usefulness of this product is for evaluating particles within air, it will, of course,  
20 be understood that the instrument is useful in detecting particles in other gases as well. Since the dimensions and parameters given below concern airborne particles, it is possible that some changes in the instrument may be required for other gases, but the same principles are  
25 employed. The nozzle 18 directs the sample air jet 19 into the main sensor cell 10, at an angle of 90° with respect to the light beam 14, with the nozzle being situated so that the air jet 19 emanating from it will pass through the light beam. A control air duct 24  
30 surrounds the nozzle and also extends into the main sensor cell body. A sample air exhaust nozzle 26 extends through the wall of the sensor cell body opposite of that of the inlet nozzle 18. A purge air inlet 30 is located adjacent one end of the laser plasma tube Brewster window 13 and a  
35 second purge air inlet 32 is located near the cavity end mirror 16.

-5-

Typically, the sensor cell 10 is sealed and sample air is introduced through the nozzle by means of a vacuum pump 36 connected to the sample exhaust 26. A portion of the air drawn in through the nozzle 18 and out through the exhaust 26 is recirculated through a filter 38 and into the control air duct 24 surrounding the nozzle 18. Also a portion of the filtered air is introduced to the two purge air inlets 30 and 32 which direct clean flows of air in a manner to prevent contaminants from engaging critical optical surfaces in the system. The purge air also exits from the cell through the sample exhaust 26. Sample air is passed through a filter 48 to an exhaust 37. The amount of air allowed to pass through the filter 38 is controlled by adjusting the valve 45 which is connected in parallel with the pump 36 to allow recirculation of a portion of the pump output. The valve 49 downstream from the pump 36 controls the sample gas flow rate.

Thus, in accordance with the general operation of an optical particle counter, the air to be sampled is introduced through the nozzle 18, intersects the light beam 14 and is exhausted through the sample exhaust 26. As the sample air jet is directed through the light beam, the particles in the beam scatter some of the light and these scattered light signals, schematically shown at 39 in Figure 2, are collected by suitable detection means schematically illustrated by the broken line 35 in Figure 1. As is typical for many light scattering sensors, the detection means is also centrally located at 90° with respect to the light beam axis 15, as indicated in Figures 1 and 2. Various forms of detection equipment are known to those skilled in the art and hence they are not described in detail herein. Also apparatus of this type is available from the assignee of this invention. A portion of the optics of such detection means is schematically illustrated in Figure 2 by a mirror 40 on one side of the beam receiving signals 39, and a lens 42

-6-

receiving reflected signals from the mirror and receiving direct signals from the scattered light.

As indicated above, it is important that the sample air jet be precisely controlled so as to provide uniform, laminar flow with a consistent and precise cross section as the jet passes through the light beam. In accordance with the present invention, this is primarily accomplished by the unique geometry of the air inlet nozzle. The result is further enhanced by utilizing the nozzle in combination with the control air duct.

As seen in Figure 3, the inlet nozzle 18 has an upstream tubular portion 18a with a circular cross section, and a downstream flattened tip 18b connected to the tubular portion 18a by a smoothly tapered transition section 18c. As may be seen from Figures 3 and 4, the flattened tubular tip has a generally rectangular cross section. The longer sides of the cross section are precisely parallel although the ends of the cross section are rounded, as seen in Figures 6 and 7. Thus, it might be said that the cross section has somewhat of an elongated racetrack cross section.

As seen from Figure 4, the interior shorter dimension of the nozzle tip cross section is smaller than the diameter of the laser beam so that the entire air jet will pass through the beam. More specifically, the shorter dimension is less than or equal to about one half the beam diameter in two versions of the invention scheduled for production. The longer dimension of the tip cross section is selected to provide sufficient sample airflow at an acceptable velocity. Also, the longer dimension must be kept within the accuracy limits of the radiation detecting optics. These parameters determine the diameter of the tubular portion of the nozzle which is required to provide the needed tip portion, with the tip being formed by flattening the end of the tubular portion. As may be seen, the longer dimension of the nozzle tip cross section

-7-

is much greater than the shorter dimension. In one form of the invention scheduled for production, the laser beam is about .06 inch diameter. The nozzle tip to be used with that laser is illustrated in Figure 6 and has a shorter interior dimension  $z$  of about .03 inch, while the longer interior dimension  $y$  is .45 inch. Thus, the longer dimension is about fifteen times greater than the shorter dimension. In another form of the invention, the laser beam has a diameter of about .02 inch, and the lower flow nozzle to be used with it, shown in Figure 7, has an interior shorter dimension  $z'$  of only about .01 inch, such that the longer dimension  $y$  is about 45 times greater. From these examples, the extreme thin, flat nature of the air jet emanating from the nozzle can be appreciated.

15 The entire flattened tip of the nozzle up to the transition section 18c has a constant cross section. In the high volume flow form of the invention in Figure 6, this dimension  $x$  is approximately 2.25 inches. In a version of the nozzle shown in Figure 7, this dimension  $x$  is 1.5 inches. Thus, it can be stated that in one form of the invention, the length of the constant cross section flattened tip portion is about five times greater than the longer dimension of the nozzle tip cross section, and about three times greater than the nozzle tip cross section in the second mentioned form of the invention.

In the forms of the invention shown in Figures 6 and 7, the nozzle tubular portions 18a have a circular cross section of about .29 inch. Since this diameter is related to the longer dimension of the nozzle tip cross section, 30 it may also be meaningful to state that the length of the flattened tip portion 18b is almost eight times greater than the inner diameter in one form of the invention and more than five times greater than the tube inner diameter in the other form mentioned. Thinness of the jet is also 35 important from a standpoint of laminar flow. Relating the axial length of the constant cross section of the tip to

-8-

the shorter dimension of the tip, it can be stated that, in the Figure 6 form of the invention, the 2.25 inch length is about 75 times greater than the shorter dimension. In the form of the invention shown in Figure 5 7, the 1.5 inch length is about 150 times greater than the .01 inch shorter interior dimension of the tip cross section. Preferably, the length of the flattened tip is at least 50 times greater than the shorter dimension of the jet. Thus, again, the flat laminar flow of the 10 resulting jet can be appreciated.

The necessary length of the flattened tip is related to the flow rate through the nozzle, a longer tip being required for higher flow rates to obtain the desired laminar flow. Increasing the length of the flattened 15 portion 18b improves the laminar flow of the air jet. However, there is, of course, an offsetting pressure drop accompanying an increase in the length. Also, increasing the length increases the difficulty of making the nozzle with the desired precision. It is believed that the 20 flattened tip length should be at least .5 inch to obtain the desired laminar flow with lower flow rates, and greater than that for higher flow rates.

As indicated above, the shorter dimension of the tip cross section is dictated by the laser beam diameter. 25 Providing a laser beam of increased diameter would require less flattening of the tube such that an adequate airflow could possibly be obtained with a smaller diameter tube with circular cross section. However, increasing intracavity laser beam diameter represents a substantial 30 complexity regarding instrument sensitivity, laser resonator design, and coordination with the associated optics and electronics. In general, smaller beam diameters are desirable from a standpoint of beam power density, and are required in high-sensitivity instruments. 35 The control air duct further enhances stability and consistency of the laminar nature of the air jet. The

-9-

control air moves at a velocity considerably less than the sample air jet. The control air serves as a curtain or sheath of air surrounding the faster moving jet. This sheath tends to confine and resist movement of the air jet out of its laminar flow pattern. It should be noted, however, that the control air sheath does not restrict the cross section of the air jet. That is, it does not perform an aerodynamic focusing function, but merely a confining function as it inhibits excessive entrainment and mixing of the sample jet and surrounding medium. Since the control air has been filtered, such air sheath does not add further particles to the sample air, even if there should be some slight mixing at a point further downstream from the exit of the nozzle.

From the standpoint of maximizing scattered light signal strength, it is desirable to use a thin nozzle to minimize light obstruction. A thin wall also helps maintain laminar jet flow by minimizing turbulence at the tip outlet. In the forms of the invention referred to above, the wall thickness is about .01 inch. The use of thin wall material also insures a thin, uniform tip edge that aids laminar jet flow and flow stability.

It is also important that the nozzle air jet forming surfaces be formed to foster laminar flow. Thus, preferably, the inside surface of the nozzle has a smooth, almost reflective finish.

Since the thrust of the invention is to obtain uniform, laminar air jet flow through the light beam, it is desirable to position the end of the nozzle flat portion 18b close to the beam, but at the same time, the nozzle and the flow tube 24 should not appreciably block scattered light signals or introduce additional stray light levels that could adversely affect the sensitivity or accuracy of the readings obtained. In the arrangement of Figures 4 and 5, which illustrates the beams of about .06 diameter, the tip of the nozzle is about 1/8 inch from

-10-

the center of the beam. Note that the nozzle extends slightly closer to the beam than does the co-flow tube 24.

An other parameter of a practical particle counter is that sufficient sample flow volume must be provided to obtain rapid readings. With the larger cross sectional area of the nozzle of Figure 6, a flow can be obtained of up to one cubic foot per minute, which is considered high flow. The nozzle of Figure 7 is projected to provide about .1 cubic foot per minute, which is considered moderate flow. The more accurate and sensitive particle counters (e.g., aerosol spectrometers) typically have low flow rates, in the range of .01 cubic foot per minute. With the nozzle of the present invention, high flow rates with low turbulence are provided, thus increasing accuracy, sensitivity, and more statistically significant readings.

-11-

WHAT IS CLAIMED IS:

1. An instrument for analyzing and counting particles in air or other gas, comprising a system for transmitting a jet of gas through a concentrated light beam in a test cell so as to illuminate the jet and cause light to be scattered by particles in the jet, said system including a gas inlet nozzle forming and directing the jet into the test cell, said nozzle having a flattened, thin walled tip portion with a generally rectangular interior cross section that produces a thin flat jet in which the longer dimension of the cross section of the jet is much greater than the shorter dimension, and the length of said nozzle flattened portion is at least three times greater than said cross section longer dimension, with the result being that the jet formed by the nozzle has very laminar flow as it passes through said beam.

2. The instrument of Claim 1 wherein said nozzle has an upstream tubular portion of circular cross section joined to said flattened tip portion by a very smoothly tapered transition portion.

3. The instrument of Claim 2 wherein said flattened portion is formed by flattening the end of the tubular portion.

4. The instrument of Claim 1 wherein the shorter dimension of said jet cross section is less than or approximately equal to half the cross sectional dimension of the light beam through which the jet passes.

5. The instrument of Claims 1, 2, 3 or 4 including a duct surrounding and spaced outwardly from said nozzle to conduct a sheath of air surrounding the jet and the nozzle so as to help confine the jet and resist the creation of turbulence.

6. The instrument of Claim 5 wherein said nozzle tip extends slightly beyond the end of said duct.

-12-

7. The instrument of Claim 1 wherein the longer dimension of the jet cross section is more than 10 times greater than the shorter dimension.

8. The instrument of Claim 1 wherein the length of  
5 said flattened tip portion is at least .5 inch.

9. A particle counter comprising:

means forming a test cell for illuminating and detecting particles in a gas stream;

10 means providing a high intensity light beam passing through the test cell;

means for introducing a sample jet of gas transversely through the light beam; and

15 means for detecting and measuring light scattered from particles carried by the jet and illuminated by the light beam;

said jet introducing means, including an inlet nozzle having a thin wall tubular portion which tapers smoothly to an elongated, flattened tip portion having a constant cross section which causes the jet to have  
20 a corresponding flattened, generally rectangular cross section with the shorter dimension of the cross section extending perpendicular to the light beam optical axis and being less than the diameter of the light beam, and with the longer dimension of the jet  
25 cross section extending in the direction of the light beam, the axial length of said flattened tip portion extends at least .5 inch, whereby the jet has an extremely laminar flow.

10. The instrument of Claim 9 wherein the wall  
30 thickness of said nozzle is about .01 inch.

11. The instrument of Claim 9 wherein the interior surface of said tube and tip portion is extremely smooth and free of blemishes that might cause turbulence in the air jet.

-13-

12. The instrument of Claim 9 wherein the axial length of said flattened tip is more than 50 times greater than the shorter dimension of said jet.

13. The instrument of Claim 9 wherein the axial  
5 length of said flattened tip is approximately 2.25 inches.

14. The instrument of Claim 13 wherein the shorter dimension of said tip cross section is about .03 inch.

15. The instrument of Claim 9 wherein the axial length of said flattened tip is approximately 1.5 inches.

10 16. The instrument of Claim 15 wherein the shorter dimension of said tip cross section is approximately .01 inch.

17. The instrument of Claim 9 including a gas outlet nozzle in said cell, a duct surrounding and spaced from  
15 said inlet nozzle, a pump connected to said outlet nozzle and to an exhaust line, to draw sample gas flow into said cell through said inlet nozzle, a valve in said line to control the inlet gas flow, a conduit recirculating a portion of the pump output to said duct so that a sheath  
20 of gas flows into said cell around said jet, a conduit connected in parallel to said pump with a valve in said conduit whereby a portion of the pump output is recirculated to the pump inlet to thereby control the flow through said duct, and a particle filter for filtering  
25 particles from the gas fed to said duct.

1/1

FIG. 1




FIG. 2




FIG. 6




FIG. 3




FIG. 7




FIG. 4





FIG. 5



# INTERNATIONAL SEARCH REPORT

International Application No PCT/US87/00916

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (If several classification symbols apply, indicate all) <sup>3</sup> According to International Patent Classification (IPC) or to both National Classification and IPC IPC (4): GOIN 21/53 U.S. CL. 356/338																				
<b>II. FIELDS SEARCHED</b> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">Minimum Documentation Searched <sup>4</sup></div> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 20%; text-align: left; border-bottom: 1px solid black;">Classification System</th> <th style="text-align: left; border-bottom: 1px solid black;">Classification Symbols</th> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px;">U.S.</td> <td style="padding: 5px;">356/335-342; 250/574, 576; 239/86, 290, 291, 299, 300</td> </tr> </table> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched <sup>5</sup></div>			Classification System	Classification Symbols	U.S.	356/335-342; 250/574, 576; 239/86, 290, 291, 299, 300														
Classification System	Classification Symbols																			
U.S.	356/335-342; 250/574, 576; 239/86, 290, 291, 299, 300																			
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT</b> <sup>14</sup> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 10%; text-align: left; border-bottom: 1px solid black;">Category <sup>6</sup></th> <th style="text-align: left; border-bottom: 1px solid black;">Citation of Document, <sup>15</sup> with indication, where appropriate, of the relevant passages <sup>17</sup></th> <th style="text-align: left; border-bottom: 1px solid black;">Relevant to Claim No. <sup>18</sup></th> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;">Y</td> <td style="border-right: 1px solid black; padding: 5px;">US, A, 4,571,079 (KNOLLENBERG) 18 FEBRUARY 1986 See the entire document.</td> <td style="padding: 5px;">1-17</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;">A</td> <td style="border-right: 1px solid black; padding: 5px;">US, A, 4,343,551 (EISERT) 10 AUGUST 1982, See columns 1 and 2.</td> <td style="padding: 5px;">2, 3, 5, 6, 9</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;"><math>\frac{Y}{A}</math></td> <td style="border-right: 1px solid black; padding: 5px;">US, A, 3,840,304 (HIRAFUJI) 08 OCTOBER 1974, See column 2 lines 55 to the end and columns 3 and 4.</td> <td style="padding: 5px;"><math>\frac{9, 11, 17}{2, 3, 5, 6}</math></td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;">A</td> <td style="border-right: 1px solid black; padding: 5px;">US, A, 3,766,489 (ROSENBERG ET AL.) 16 OCTOBER 1973 See columns 2, 3 and 4.</td> <td style="padding: 5px;">2, 3; 5-8, 10-16</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;">Y</td> <td style="border-right: 1px solid black; padding: 5px;">US, A, 2,535,181 (WAY) 26 DECEMBER 1950, See entire document</td> <td style="padding: 5px;">2, 3, 9-11</td> </tr> </table>			Category <sup>6</sup>	Citation of Document, <sup>15</sup> with indication, where appropriate, of the relevant passages <sup>17</sup>	Relevant to Claim No. <sup>18</sup>	Y	US, A, 4,571,079 (KNOLLENBERG) 18 FEBRUARY 1986 See the entire document.	1-17	A	US, A, 4,343,551 (EISERT) 10 AUGUST 1982, See columns 1 and 2.	2, 3, 5, 6, 9	$\frac{Y}{A}$	US, A, 3,840,304 (HIRAFUJI) 08 OCTOBER 1974, See column 2 lines 55 to the end and columns 3 and 4.	$\frac{9, 11, 17}{2, 3, 5, 6}$	A	US, A, 3,766,489 (ROSENBERG ET AL.) 16 OCTOBER 1973 See columns 2, 3 and 4.	2, 3; 5-8, 10-16	Y	US, A, 2,535,181 (WAY) 26 DECEMBER 1950, See entire document	2, 3, 9-11
Category <sup>6</sup>	Citation of Document, <sup>15</sup> with indication, where appropriate, of the relevant passages <sup>17</sup>	Relevant to Claim No. <sup>18</sup>																		
Y	US, A, 4,571,079 (KNOLLENBERG) 18 FEBRUARY 1986 See the entire document.	1-17																		
A	US, A, 4,343,551 (EISERT) 10 AUGUST 1982, See columns 1 and 2.	2, 3, 5, 6, 9																		
$\frac{Y}{A}$	US, A, 3,840,304 (HIRAFUJI) 08 OCTOBER 1974, See column 2 lines 55 to the end and columns 3 and 4.	$\frac{9, 11, 17}{2, 3, 5, 6}$																		
A	US, A, 3,766,489 (ROSENBERG ET AL.) 16 OCTOBER 1973 See columns 2, 3 and 4.	2, 3; 5-8, 10-16																		
Y	US, A, 2,535,181 (WAY) 26 DECEMBER 1950, See entire document	2, 3, 9-11																		
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p><sup>13</sup> Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"Δ" document member of the same patent family</p> </div> </div>																				
<b>IV. CERTIFICATION</b> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border-bottom: 1px solid black; padding: 5px;">Date of the Actual Completion of the International Search <sup>1</sup></td> <td style="width: 50%; border-bottom: 1px solid black; padding: 5px;">Date of Mailing of this International Search Report <sup>2</sup></td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 5px;">17 JUNE 1987</td> <td style="border-bottom: 1px solid black; padding: 5px;">04 AUG 1987</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 5px;">International Searching Authority <sup>1</sup></td> <td style="border-bottom: 1px solid black; padding: 5px;">Signature of Authorized Officer <sup>20</sup></td> </tr> <tr> <td style="padding: 5px;">ISA/US</td> <td style="padding: 5px;">F.N. Samuels</td> </tr> </table>			Date of the Actual Completion of the International Search <sup>1</sup>	Date of Mailing of this International Search Report <sup>2</sup>	17 JUNE 1987	04 AUG 1987	International Searching Authority <sup>1</sup>	Signature of Authorized Officer <sup>20</sup>	ISA/US	F.N. Samuels										
Date of the Actual Completion of the International Search <sup>1</sup>	Date of Mailing of this International Search Report <sup>2</sup>																			
17 JUNE 1987	04 AUG 1987																			
International Searching Authority <sup>1</sup>	Signature of Authorized Officer <sup>20</sup>																			
ISA/US	F.N. Samuels																			

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET

SECRET